

## Digital temperature/humidity probe, cable 5 m

code: DIGIL/M-5



Digital probe with connector MiniDIN.

Stainless steel mesh filter.

The probe is supplied with a calibration certificate.

The probe is interchangeable without calibration to a specific device and regardless of the length of the cable.

**Optionally also available with cable of various lengths. For other cable lengths use the selector.**

### Technical data

|                            |  |
|----------------------------|--|
| TEMPERATURE SENSOR         |  |
| Measuring range            | -30 to +105 °C   |
| Accuracy                   | ±0.4 °C  |
| Response time              | t90 < 6 min, temperature step 20 °C, air flow 1 m/s    |
| HUMIDITY SENSOR            |  |
| Measuring range            | 0 to 100 % RV  |
| Accuracy                   | ±1.8 %RV in the range of 0 to 90 % RH at 23 °C         |
| Response time              | t90 < 9 s (humidity step 60 %RH, constant temperature) |
| Hysteresis                 | ±1 % RV  |
| Linearity                  | ±1 % RV  |
| DEW POINT                  |  |
| Measuring range            | -60 to +80 °C  |
| Accuracy                   | see the manual   |
| &n GENERAL TECHNICAL DATA  |  |
| Operating temperature      | -30 to +105 °C   |
| Protection class           | IP40   |
| Connector                  | ELKA   |
| Dimensions (without cable) | 88 x 18 mm   |
| Cable length               | 1 m, 2 m, 5 m, 10 m or 15 m                            |
| Weight                     | cca 55 g   |
| Warranty                   | 3 years  |