

Compressed air temperature and humidity regulator with 230Vac/8A relays

code: H3061P



Humidistat, thermostat with two relay outputs. T+RH probe from hard anodized duralumin for compressed air up to 25 bars with 1 meter cable. Outdoor, indoor use.

Relative humidity, temperature probe on a cable. Measured values are also converted to other humidity interpretation: dew point temperature, absolute humidity, specific humidity, mixing ratio, specific enthalpy.

Technical data

| | |
|--|--|
| TEMPERATURE SENSOR | |
| Measuring range | -30 to +105 °C |
| Accuracy | ±0.4 °C |
| Resolution | 0.1 °C |
| HUMIDITY SENSOR | |
| Measuring range | 0 to 100 % RH |
| Accuracy | ±2.5 % RH from 5 to 95 % at 23 °C |
| Resolution | 0.1% RH |
| DEW POINT | |
| Measuring range | -60 to +80 °C |
| Accuracy | ±1.5 °C at ambient temperature T <25 °C and RH >30 % |
| Resolution | 0.1 °C |
| MEASURING THE MOISTURE OF COMPRESSED AIR | |
| Measuring range | up to 25 bars |
| Air flow velocity | up to 25 m/s at a pressure of 1 bar (1m/s at a pressure of 25 bar) |
| RELAY OUTPUTS | |
| Quantity | 2 |
| Maximal voltage | 250 VAC |
| Maximal current | 8 A |
| Maximal power | 2000 VA AC, 192 W DC |
| GENERAL TECHNICAL DATA | |
| Operating temperature | -30 to +80 °C |
| Channels | 1x connectable temperature+humidity probe |
| Counted values | dew point, absolute humidity, specific humidity, mixing ratio, specific enthalpy |

| | |
|-----------------------------|--|
| Acoustic alarm | from built-in beeper - switchable |
| Power | 110-240 VAC |
| Protection class | IP65 electronics; IP40 sensors |
| Dimensions | 136 x 161 x 45 mm; length/diameter of external probe 88/18 mm |
| External probe cable length | 1 meter |
| Weight | approx. 490 g |
| Warranty | 3 years |