

## Pt1000TG7/M, temperature probe, cable 5 m

code: SN166M

Temperature probe with Pt1000 sensor.

Brass surface probe with cable of specified length, with MiniDIN connector. Range from -30 to +200°C, accuracy  $\pm(0,15+0,002 |t|)$ . Diameter 18mm, width 6.5mm, 2wires.

Mounting by a M4 srew or fixing by a self adhesive tape. IP65 protection.

**Optionally also available with cable of various lengths. For other cable lengths use the selector.**



### Technical data

TEMPERATURE SENSOR	
Measuring range	-50 to +200 °C
Accuracy	$\pm (0.15 + 0.002 t)$ at °C
Accuracy class	A
Time response	$t_{0.5} < 10$ s (on flat surface of Al prism without paste)
Type of sensing element	Pt1000
Temperature coefficient	3850 ppm / °C
GENERAL TECHNICAL DATA	
Wire connection	2-wire connection
Material of the case	brass
Dimensions of the case	height $6 \pm 0.1$ mm;  diameter $19.5 \pm 0.1$ mm;  mounting holes diameter $4.3 \pm 0.05$ mm
Lead-in cable	silicone shielded
Length of lead-in cable	5 meters
Connector	MiniDin
IP protection	IP65
Warranty	30 months