

# WebSensor with PoE - remote temperature, humidity, CO2 concentration with Ethernet interface

code: T6640



CO2 - carbon dioxide t-line Web sensor. Remote alarm.

Web Sensor with built-in temperature, humidity, CO<sub>2</sub> sensor with PoE function.

A multiple point CO<sub>2</sub> and temperature adjustment procedure leads to excellent CO<sub>2</sub> measurement accuracy over the entire temperature working range; this is a must for process control and outdoor applications. The dual wavelength NDIR CO<sub>2</sub> sensing procedure compensates automatically for ageing effects. The CO<sub>2</sub> module is highly resistant to pollution and offers maintenance free operation and outstanding long term stability.

The CO<sub>2</sub> concentration is shown on the display or signaled by a color LED.

### Processing and analysis of measured data:

- online in [COMET Cloud](#)
- [COMET Database](#) software
- [integration into 3-party systems](#)

### Possibility to [extend the measuring range](#) for an additional charge:

- Measuring range: 0 to 10 000 ppm
- Accuracy: 100 ppm + 5% of the measured value at 25 °C and 1013 hPa

### Technical data

TEMPERATURE SENSOR	
Measuring range	-30 to +80 °C
Accuracy	±0.6 °C
Resolution	0.1 °C
HUMIDITY SENSOR	
Measuring range	0 to 100 % RH
Accuracy	± 2,5 % RH
Resolution	0.1% RH
DEW POINT	
Measuring range	-60 to +80 °C
Accuracy	±1.6°C at ambient temperature T<25°C and RH>30%
Resolution	0.1 °C
CO2 SENSOR	
Measuring range	0 to 2000 ppm
Accuracy	±(50ppm +2% from reading) at 25°C and 1013hPa
Resolution	1 ppm
GENERAL TECHNICAL DATA	
Operating temperature	-30 to +60 °C
Channels	internal temperature, humidity and CO <sub>2</sub> sensor

Counted values	dew point, absolute humidity, specific humidity, mixing ratio, specific enthalpy
Output	Ethernet
Measuring interval	2 s; CO <sub>2</sub> 15 s
Range of humidity sensor temperature compensation	all temperature range
Communication protocol	WWW, ModbusTCP, SNMPv1, SOAP, XML
Alarm protocols	E-mail, SNMP Trap, Syslog
Power	Power over Ethernet according to IEEE 802.3af or 5Vdc
Protection class	IP30 electronics, IP40 sensors
Dimensions	136 x 117 x 45 mm
Weight	approx. 150 g
Warranty	3 years