

# IoT Wireless Temperature and Relative Humidity Datalogger with connector for other temperature probe, with built-in 4G modem and Flat Rate SIM Card

code: U3631Gsim



IoT Wireless Datalogger kit with built-in GSM modem and Flat Rate SIM Card allows the instant connection to the COMET Cloud. Measured values can be sent to the internet storage [COMET Cloud](#), which is a complete monitoring, alarm and analysis system. In case of exceeded set limits e-mail is sent from the [COMET Cloud](#).

Alarms are also indicated locally by LED, LCD and acoustically by built-in beeper.

The recording is performed in a non-volatile electronic memory. The data can be transferred to a PC via included USB-C cable.

GSM recorder **includes Traceable calibration certificate** with declared metrological traceability of etalons is based on requirements of **EN ISO/IEC 17025 standard**.

## Technical data

TEMPERATURE SENSOR	
Measuring range	-20 to +60 °C
Accuracy	±0.4 °C
Resolution	0.1 °C
TEMPERATURE SENSOR - external probe Pt1000	
Measuring range	-90 to +260 °C
Accuracy	±0.2 °C (-50 to +100 °C); ±0.2 % from reading from +100 to +260 °C; ±0.4 % from reading from -90 to -50 °C
Resolution	0.1 °C
HUMIDITY SENSOR	
Measuring range	0 to 100 % RH
Accuracy	± 1.8 % RH
Resolution	0.1% RH
DEW POINT	
Measuring range	-90 to +60 °C
Accuracy	±1.5 °C at ambient temperature T <25 °C and RH >30 %
Resolution	0.1 °C
GSM MODEM PARAMETERS	
LTE Cat 1	LTE FDD/GSM/GPRS/EDGE
Supported network types	GSM/GPRS/EDGE 900/1800 MHz  LTE FDD B1/B3/B5/B7/B8/B20
GENERAL TECHNICAL DATA	
Operating temperature	-20 to +60 °C
Channels	internal temperature and humidity sensor, 1x external temperature probe
Memory	500,000 values in noncyclic logging mode; 350,000 values in cyclic record mode

Recording interval to the internal memory	adjustable from 1 second to 24 hours
Recording interval to the COMET Cloud	from 5 minutes
Interval for measuring and evaluating alarms	adjustable 1 s, 10 s, 1 min
Recording mode	noncyclic - data logging stops after filling the memory cyclic - after filling memory oldest data is overwritten by new
Real time clock	year, leap year, month, day, hour, minute, second
Power	rechargeable Li-Ion battery A8200, 3.6V/5200mAh
Protection class	IP67 electronics; IP30 sensors
Dimensions	61 x 93 x 53 mm, with antenna 120 x 93 x 53 mm
Weight (including batteries)	approx. 260 g
Warranty	3 years